

Mobile Stables

Timber sizes nominal before planning and processing, other dimensions may vary dependant on individual building.

Harrier Range

Ridge Height:	3.0m excluding Onduline
Eaves Height:	2.4m excluding Onduline
Threshold Height:	80mm
Opening Size:	1.880m (w) x 2.090m (h) – from ground to top of opening is 2.170m
Overhang:	1050mm overhang lined with plywood (1200mm with gutter)
Skid:	80 x 40mm galvanised skid with towing points at either end
Framework:	Constructed from ex75x50mm cls tanalith E treated timber at 600mm centres. Studwork doubles at door apertures, additional cross members at 1.22m height.
Cladding:	Premium ex19x125mm tanalith E treated overlap shiplap, fixed with 45mm sheradized ring shanked nails
Kick-boarding:	Lined to 1.22m with 18mm OSB
Roof trusses:	All trusses fixed to sections with 100mm or 150mm timber lock screws
Purlins:	47x100mm or 47x125mm C24 positioned at a maximum of 600mm centres dependant on roof span
Roofing:	Black Onduline with Onduline ridge capping lined with 11mm OSB
Guttering:	112mm black uPVC guttering fitted with 68mm downpipes to both ends of front elevation
Windows:	Nil
Stable Doors	Approx. 1220mm(w) x 2130(h) x 56mm (to fit 1230mm opening) Constructed as follows: <ul style="list-style-type: none">• Top and Bottom door• Clad with ex19x125mm V jointed tongue & grooved planed timber• 150x28mm braced framework• All ironmongery is hot dipped galvanised• Heavy 600mm hinges• 50mm chew strip to top of bottom door• Lined internally with 12mm exterior grade plywood• Brenton bolt to top door• Kick-over latch• Cabin hooks to both doors• 200mm Auto animal bolt to bottom door• Bottom door height 1200mm

Mobile Combination units

(As mobile stable with the following differences for the Tack room section)

Opening:	Tackroom door width 0.90m wide x 2.1m high
Interior Lining:	Membrane lined 95g
Door:	Supplied and fitted with three 16" T hinges, 6" Brenton bolt and cabin hook to secure door when open.
Floor:	47x100mm C24 tanalith E treated joists at a maximum 600mm centres. Covered with 125x22mm sawn tanalith E treated floorboards or 18mm OSB
Roof lining:	Face of truss between stable and tack room also boarded with 11mm OSB

Mobile Tack room

(As mobile stable with the following differences)

Interior Lining:	All walls are fully lined to eaves height with 11mm OSB
Door:	Supplied and fitted with three 16" T hinges, 6" Brenton bolt and cabin hook to secure door when open.
Floor:	47x100mm C24 tanalith E treated joists at a maximum 600mm centres. Covered with 150 x 28mm sawn Tanalith E treated floorboards
Roof lining:	11mm OSB.