

# Mobile Stables

Timber sizes nominal before planning and processing, other dimensions may vary dependant on individual building.

## Hawk Range

Eaves Height:	2.34m excluding Onduline
Ridge Height:	2.89m excluding Onduline
Threshold Height:	113mm
Opening Size:	1.880m (w) x 2.010m (h) – from ground to top of opening is 2.143m
Overhang:	650mm overhang (3m deep models), 1.05m overhang (on 3.6m deep models)
Skid:	150x75mm tanalith E treated skid with galvanised steel towing points at either end
Framework:	Constructed from ex75x50mm cls tanalith E treated timber at 600mm centres. Studwork doubles at door apertures, additional cross members at 1.22m height.
Cladding:	Premium ex16mm tanalith E treated overlap shiplap
Kick-boarding:	Lined to 1.22m with 11mm OSB
Roof trusses:	Constructed from 100x50mm CLS Tanalith E Treated timber. All trusses fixed to sections with 100mm or 150mm timber lock screws
Purlins:	47x100mm C24 positioned at a maximum of 550mm centres
Roofing:	Black Onduline with Onduline ridge capping
Guttering:	Nil
Windows:	Nil
Stable Doors	Approx. 1220mm(w) x 2130(h) x 56mm (to fit 1230mm opening) Constructed as follows: <ul style="list-style-type: none"><li>• Bottom door only</li><li>• Clad with ex19x125mm V jointed tongue &amp; grooved planed timber</li><li>• 150x28mm braced framework</li><li>• All ironmongery is hot dipped galvanised</li><li>• Heavy 450mm hinges</li><li>• 50mm chew strip to top of bottom door</li><li>• Lined internally with 12mm exterior grade plywood</li><li>• Brenton bolt to top door</li><li>• Kick-over latch</li><li>• 200mm Auto animal bolt to bottom door</li><li>• Bottom door height 1200mm</li></ul>

## Mobile Combination units

*(as field shelter with the following differences for the Tack room section)*

Opening:	Tackroom door width 0.9m wide x 2.1m high
Interior Lining:	Membrane lined 95g
Door:	Supplied and fitted with three 16" T hinges, 6" Brenton bolt and cabin hook to secure door when open.
Floor:	47x100mm tanalith E treated joists at a maximum 600mm centres. Covered with 18mm OSB floorboards
Roof lining:	Face of truss between stable and tack room also boarded