

Mobile Stables

Timber sizes nominal before planning and processing, other dimensions may vary dependant on individual building.

Hunter Range

Ridge Height:	3.01m excluding Onduline
Eaves Height:	2.46m excluding Onduline
Threshold Height:	138mm
Opening Size:	1.22m (w) x 2.09m (h) – from ground to top of opening is 2.228m
Overhang:	With 1.2m overhang lined with plywood (1.35m with gutter)
Skid:	100x100mm galvanised skid with towing points at either end
Framework:	Constructed from ex100x50mm CLS tanalith E treated timber at 600mm centres. Studwork doubles at door apertures. Additional 100x50mm cls cross members at 1.22m height.
Cladding:	Premium ex19x125mm tanalith E treated overlap shiplap, fixed with 45mm sheradized ring shanked nails
Kick-boarding:	Lined to 1.22m with 12mm plywood
Roof trusses:	All trusses fixed to sections with 100mm or 150mm timberlock screws
Purlins:	47x100mm or 47x125mm C24 positioned at a maximum of 600mm centres dependant on roof span
Roofing:	Black Onduline with Onduline ridge capping lined with 11mm OSB
Guttering:	112mm black upvc guttering fitted with one 68mm downpipe to either end of front elevation
Windows:	Nil
Stable Doors	Approx. 1220mm(w) x 2130(h) x 56mm (to fit 1230mm opening) Constructed as follows: <ul style="list-style-type: none">• Top and Bottom door• Clad with ex19x125mm V jointed tongue & grooved planed timber• 150x28mm braced framework• All ironmongery is hot dipped galvanised• Heavy 600mm hinges• 50mm chew strip to top of bottom door• Top door frame protection fitted• Lined internally with 12mm exterior grade plywood• Brenton bolt to top door• Kick-over latch• Cabin hooks to both doors• 200mm Auto animal bolt to bottom door• Bottom door height 1200mm

Mobile Combination units

(As mobile stable with the following differences for the tack room section)

Opening:	Tack room door width 0.90m wide x 2.1m high
Interior Lining:	Membrane lined 95g
Door:	Supplied and fitted with three 600mm T hinges, 150mm Brenton bolt and cabin hook to secure door when open.
Floor:	100x47mm C24 tanalith E treated joists covered with 125x22mm sawn Tanalith E treated floorboards or 18mm OSB
Roof lining:	Face of truss between stable and tack room also boarded with hardwood faced ply.

Mobile Tack room

(As mobile stable with the following differences)

Interior Lining:	All walls are fully lined to eaves height with 9mm hardwood faced ply
Door:	Supplied and fitted with three 24" T hinges, 6" Brenton bolt and cabin hook to secure door when open.
Floor:	100x47mm Tanalith E treated joists covered with 125 x 22mm sawn Tanalith E treated floorboards or 18mm OSB
Roof lining:	11mm OSB