

Mobile Field Shelter - Harrier

Timber sizes nominal before planning and processing, other dimensions may vary dependant on individual building.

Ridge Height:	3.0m
Eaves Height:	2.4m
Threshold Height:	80mm
Opening Size:	1.880m (w) x 2.090m (h) – from ground to top of opening is 2.170m
Overhang:	1050mm overhang lined with plywood (1200 mm inc gutter)
Skid:	80 x 40mm galvanised skid with towing points at either end
Framework:	Constructed from 75x50mm cls tanalith E treated timber at 600mm centres. Studwork doubles at door apertures, additional cross members at 1.22m height.
Cladding:	Premium ex19x125mm tanalith E treated overlap shiplap, fixed with 45mm sheradized ring shanked nails
Kick-boarding:	Lined to 1.22m with 18mm OSB
Roof trusses:	All trusses fixed to sections with 100mm or 150mm timber lock screws
Purlins:	ex47 x100mm or ex 47x125mm c24 timber positioned at a maximum of 600mm centres dependant on roof span
Roofing:	Black Onduline with Onduline ridge capping lined with 11mm OSB
Guttering:	112mm black uPVC guttering fitted with 68mm downpipes to both ends of front elevation
Partition:	Not included

Mobile Combination units

(As field shelter with the following differences for the Tack room section)

Opening:	Tackroom door width 0.90m wide x 2.1m high
Interior Lining:	Membrane lined 95g
Door:	Supplied and fitted with three 16" T hinges, 6" Brenton bolt and cabin hook to secure door when open.
Floor:	ex 47x100mm tanalith E treated joists at a maximum 600mm centres. Covered with 125x22mm sawn tanalith E treated floorboards or 18mm OSB
Roof lining:	Face of truss between stable and tack room also boarded with 11mm OSB

Mobile Tack room

(As mobile field shelter with the following differences)

Interior Lining:	All walls are fully lined to eaves height with 11mm OSB
Door:	Supplied and fitted with three 16" T hinges, 6" Brenton bolt and cabin hook to secure door when open.
Floor:	ex 47x100mm tanalith E treated joists at a maximum 600mm centres. Covered with 150 x 28mm sawn Tanalith E treated floorboards
Roof lining:	11mm OSB.